

SELF-SERVICE KIOSK

KIOSK

Metallic self-service kiosk with a 32-inch touchscreen, a fast 80mm thermal ticket printer, and a 2D scanner included.



With a compact and attractive design, the metallic kiosk integrates perfectly into various commercial environments, from retail stores to high-traffic shopping centers. Featuring a 32-inch capacitive touchscreen, this device is ideal for offering an all-in-one solution.

Moreover, the interactive kiosk not only improves the speed and accuracy of transactions but also features a modern design that enhances your business's image, providing a pleasant shopping experience for customers. It comes standard with a thermal ticket printer and a 2D scanner.



KIOSK WINDOWS

TECNICAL SPECIFICATIONS

Processor	Intel® J6412, 2M Cache, 2.0 GHz
RAM Memory	8G DDR4 (Max. 16GB)
Operative System	Windows 10

STORAGE

SSD	128GB
-----	-------

POWER

Power supply	AC100 - 240V
--------------	--------------

INCLUDED ACCESORIES

Thermal printer	80 mm with 170 mm/s of speed
Scanner	2D
Card reader support	Slot for pin-pad installation

DIMENSIONS

BASE	120cm * 40cm * 64cm
WEIGHT	50.5cm * 50cm
GUARANTEE	48kg
	2 years

TOUCH PANEL

Display BOE	32-inch Portrait Orientation IPS LCD
Touch technology	Capacitive 10 points
Bright	280 Nits
Resolution	1920*1080
Contrast ratio	1200:1

PORTS I/O

USB	5
RS232 Serial	3
LAN RJ45	1
HDMI	1
AUDIO I/O	

CERTIFICATE

EMC and Security	FCC/ CE/ RoHS
------------------	---------------

COMMUNICATION

Wifi	IEEE802.11b/g/n 2.4G
------	----------------------

WORK ENVIRONMENT

Temperature in operation	0 to 40°C
Stored temperature	-20 to 60°C
Humidity	10% to 90%



DESIGN

Elegant and sturdy structure.



DISPLAY

Ultra-thin 32-inch screen.

KIOSK WINDOWS



Stability adjustment in the structure thanks to the foot whose height can be adjusted.

High-speed thermal ticket printer with auto-cut and 2D scanner included.



Option to mount the kiosk on the wall.



Premium finishes down to the smallest detail. Cable or Wi-Fi antenna outlet to improve wireless connectivity.
