

The TLM S625 handheld scanner is a lightweight and durable terminal with an **IP54 rating**, designed for the tough daily work of any business that requires a fast and continuous workflow. It allows operation with 1-line or 2-line codes, such as the increasingly popular QR code.

The device includes a stand with a metal structure to support the scanner while it is in standby mode. The TLM S625 allows for **manual**, **automatic**, **and continuous** operation to speed up the workflow.









7LM | S625 2D

TECHNICAL SPECIFICATION

Scanner Reader

Type of illumination Laser distance

Mode CPU

2D CMOS

650 nm (visible laser) - White LED

617 mm

Manual, automatic and continuous

32 bit high resolution

CODIFICATION

1D: Codebar, Code11, Code39, Code93, EAN13, EAN8.UPCA, UPCE, Code 128, Industrial of 2 to 5, Matrix 2 a 5, MSI Code, GS1 and Databar 2D: QR, Data Matrix, PDF417, Alipay invoice

PRECISION

Depth of field Accuracy Error ratio Interface Scan angle

60-220mm 0.1mm (5 mil) Less than 1/5 mill. USB-HID, RS232 45° - 65° - Rotation 360°

WORK ENVIRONMENT

Humedity Storage humedity Temperature Storage temperature

-20°C to 60°C -40°C to 70°C Certifications

CE EN55022 B FCC Part 15 Class B SGS, IP54

5%-95% RH

5%-95% RH

ELECTRICAL

Power supply Power in operation

DC 5V 135 mA **DIMENSIONS** 83 x 70 x 172 mm **MATERIAL** ABS + PC WEIGHT 112 g

RESISTANCE Drop test: 1,5 meters

GURANTEE 2 years

