

SCANNERS

TLM | S658 2D

Omnidirectional desktop scanner with an ergonomic design. Featuring 1D and 2D technology and IP54 protection.



The TLM S858 2D omnidirectional scanner is a desktop terminal designed for work in supermarkets and checkout lines, thanks to its high scanning speed for 1D and 2D codes in any position and orientation.

This device has a standard USB cable connection, and among its most important features is its IP54-rated durability, allowing it to work safely with protection against water and dust.

2D

OMNIDIRECTIONAL

USB

IP54

www.tlmsolution.com

TLM | S658 2D

SPECIFICATIONS

Reader	2D
Lector	LED Omnidirectional
Illumination	650 nm laser (visible) - White LED
Optical system	752 horizontal x 480 vertical
Laser distance	617 mm

CODIFICATION

1D: UPC/EAN, UPC/EAN con Supplementals, Bookland, SG1-128, ISBT 128, Code 39, Code 93, Full ASCII, Trioptic Code 39, Code 32, Code 11, Codebar, Matrix 2 de 5, Interleaved 2 de 5, Discrete 2 de 5, MSI, Chinese 2 de 5, GS1 Databar Variants, Korean 3 de 5, ISBT Concat

2D: PDF417, MicroPDF417, Composite Codes, TLC-39, Data Matrix, Maxi Code, QR Code, Micro QR, Aztec. U.S. Posnet and planet, U.K. Post, Janpan Post, Australian Post, Netherlands KIX Code, Royal Mai 4 state Customer, UPU FICS 4 state Postal, USPS 4CB

PRECISION

Depth of field	6-250mm
Precision	0.1mm (4 mil)
Resolution	4mil(Code 39), 75mil(Data Matrix),
Interface	5mil(PDF417)USB-HID, USB-COM,
Angle scan	RS232
	Horizontal: 46.1° Vertical: 30.4°

WORK ENVIRONMENT

Humidity	0%-95%
Storage humidity	0%-95%
Temperature	0°C-40°C
Storage humidity	-40°C-70°C
Certificacions	ISO9001, RoHS, CE FCC

ELECTRICAL

Power supply	DC 5V +- 1%
Power in operation	350 mA

DIMENSIONS

MATERIAL	96 x 108 x 150 mm
WEIGHT	ABS + PC
RESISTANCE	320 g
GUARANTEE	IP54
	2 years



OMNIDIRECTIONAL



VERTICAL ROTATION



ABS MATERIAL



USB CONNECTION