

This 7" TFT LCD display simultaneously shows text and images in full color, with a resolution of 480×234 and 64K colors. Its 400 cd/m² brightness and 120°/100° viewing angles ensure excellent visibility. Compatible with JPEG, BMP, PNG, TIF, and GIF formats, it features a 75×75 mm VESA mount and an adjustable stand for flexible installation.

It supports 11 command modes, including Logic Control, and OPOS/JPOS drivers. Featuring RS232 and USB interfaces, 0°–60° vertical rotation, and a 20×2 character display, it ensures clear and reliable presentation. With a lifespan of 30,000 hours and a 5–12 VDC power supply, it is compatible with multiple languages and complies with FCC and CE standards.







TLM TD777

SPECIFICATIONS

Display 7-inch full-color display

Panel T

 $\begin{array}{ll} \text{Number of pixels} & 480 \times 234 \text{ - RGB} \\ \text{Brightness} & 400 \text{ cd/m}^2 \\ \text{Font size} & 24 \times 24 \end{array}$

Interface RS-232 (serial) / USB
Supported image formats JPEG, BMP, PNG, TIF, GIF
Drivers OPOS/JPOS standard

Command modes ULTIMATE, EPSON, LD540, AEDEX, UTC/S, UTC/P, ADM788,

DSP800, CD5220, EMAX, LOGIC CONTROL

Supported languages English, Bosnia, Croatian, Czech, Danish, Dutch, Estonian,

Faroese, Finnish, Flemish, French, Fr Canadian, German, Greek, Hebrew, Hungarian, Icelandic, Indonesian, Irish, Italian, Katakana, Latvian, Lithuanian, Norwegian, Polish, Portuguese, Romanian, Russian, Slovene, Slovak,

Spanish, Swedish

PHYSICAL CHARACTERISTICS

Panel dimensions 154 x 86 mm

Pole dimensions Each pole: 130 x 34.5 mm Base dimensions 159,78 x 100 x 60 mm

Viewing angle Max. 90° Horizontal rotation Max. 355° Weight Aprox. 980 grams

SECURITY AND LIFESPAN

Security FCC, CE Lifespan 30,000 hours



www.tlmsolution.com