

This Zinkpos device is characterized by being unique and elegance. Made of aluminum alloy, it has a stable stand and an ultra-thin widescreen 15. 6 inches and only 10 millimeters thick.

The POS can be configured with single screen or double screen for customer, available in different sizes.

Its beautiful design makes it ideal for businesses that require special care of their image, without underestimating its power as it comes equipped with i5 processor and 8GB of RAM.

# TECHNICAL SPECIFICATION

Display: 15.6" LED True Flat Screen

Resolution: 1366\*769 CPU: Intel® i5 Dual Core

Ports: USB, COM, VGA, LAN, HDMI, Audio

Memory: DDR3 8GB Disc: M100-128GB MSATA Ethernet: 10M/100M/1000M



# **ACCESORIES AND OPTIONS**

MSR: Track 1 & 2 & 3 Second Screen: 9,7 inch Second Screen: 11,6 inch Second Screen: 15,6 inch

# GUARANTEE

3 years of guarantee

# **TECHNICAL SPECIFICATION**

**DIMENSIONS PACKAGING** WEIGHT **OPERATIVE SYSTEM GUARANTEE** 

280cm\*250cm\*360cm 445\*330\*450mm 8.2kg Windows 10 / 11

3 years

COM





 $\odot$ 











MIC AU



## **SPECIFICATIONS**

Mother board Intel® i5 Dual Core (8th GEN) Intel® i5 (8259U) Processor

**RAM Memory** 

Chipset Intel HM65 (URT) Chipset Intel HD Graphics card Graphics

#### **TOUCH PANEL**

Screen 15.6" TFT LED backlight Flat Capacitive Technology

(10 points multi touch) 300:1 Contrast, 350cd/m<sup>2</sup> Bright Bright

Resolution 1366\*769 Angle 90 to 180 degrees

## **STORAGE**

SSD M100 · 128GB (Up to 512GB)

Memory / Flash DDR3 - 8GB

## **OPTIONS**

Processor J6412 Track 1&2&3

9.7", 11,6" or 15,6" LED backlight Second screen

## PORTS I/O

USB 6×USB Serie 2 **HDMI** 

LAN 1×10/100/1000 Mbps Ethernet

VGA **AUDIO** 1/0

#### WORK ENVIRONMENT

Work temperature -10°C to 40°C -20°C to 60°C Storaged temperature Work humedity 20% to 80% Storaged humedity 20% to 90%

## **CERTIFICATE**

**EMC** et Security CE, FCC, RoHS, CB, CCC

## COMMUNICATION

Wireless LAN Option

## **POWER SUPPLY**

DC 1 2V,5A Adaptator Power supply