

PRINTER ZINKPOS 920

Printer method
Direct Thermal printer

Printer Speed
300 mm / second

Interface
USB, SERIE, ETHERNET

Operative System
iOS / Android / Windows



DESCRIPTION

This thermal ticket printer is a **compact device** with a minimalist design that requires little space. Its small size makes it perfect for environments with surface limitations, and its thermal technology ensures high-quality printing.

This thermal ticket printer has a printing speed of up to 300 mm/s. Ideal for printing tickets, receipts, and labels in retail environments, restaurants, and similar businesses.

- Available in black or white color
- Resolution 203 pp
- Certificates FCCID, CE, 3C, ROHS



OPTIONS AND ACCESORIES

Black / white color
Interface: Serial + USB + Ethernet
Wifi

GUARANTEE


2 years

zinkpos

(+34) 952 20 48 68 · www.tpvline.com · info@tpvline.com

TECHNICAL SPECIFICATION

DIMENSIONS	140 * 130 * 133 (mm)
PACKAGING	250 * 175 * 170 (mm)
WEIGHT	1100g
OPERATIVE SYSTEM	iOS / Android / Windows
GUARANTEE	2 years



SPECIFICATIONS

Printer method	Tickets térmica directa
Resolution	203 dpi
Speed	300 mm/s
Input Buffer	2048 kbytes
NV Flash	256 kbytes
Interface	USB + Serial + Ethernet (Bluetooth and WIFI optional)

CHARACTERS

Size	Font A - 12x24 Font B - 9x17
Columns	Font A - 48 columns Font B - 64 columns
Characters set	43 characters

WORK ENVIRONMENT

Work temperature	0°C ~ 45°C
Humidity	10% ~ 80%

OTHER CHARACTERISTICS

Power supply	DC 24V, 2.5A
Barcode	UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF, CODEBAR, CODE93, CODE128, QR CODE, PDF417

PAPER

Paper width	58 / 80 / 83 ± 0.5 mm
Printer width	72 / 76 / 80 / 64 / 48 / 52mm
Diameter	ΦMin: 13mm - Máx. 83 mm
Columns	576 dots/line
Line spacing	3.75 mm (Adjustable)
Paper height	0,06 - 0,08 mm

CERTIFICATE

CCC, CE, FCC, ROHS, KC, SAA, BIS, BSMI

RELIABILITY

Mechanism	6 millions of lines
TPH	150 Km
Autocutter	2 millions of cut

Driver	Windows / JPOS / Linux Android / MAC / OPOS
Emulator	ESC/POS

zinkpos

(+34) 952 20 48 68 · www.tpvline.com · info@tpvline.com